

Motor – Run – Capacitor 450 Volt

CAPACITORS

ideal solution for any type of application with single or three-phase motors supplied as single phase (Maker: COMAR)

Model 1:

Bottom M8 metal stud self-extinguishing (V2) plastic case, with bipolar cable (length 250mm) or single tag 6,3mm x 0,8mm

RATED VOLTAGE:

400 Vac - B (10.000 h) (HPFNT)
 450 Vac - C (3.000 h) (HPFPU)

RATED FREQUENCY:

50 – 60 Hz

Model 2:

Bottom M8 metal stud self-extinguishing aluminium case, with single or double tag 6,3mm x 0,8mm

RATED VOLTAGE:

450 Vac - B (10.000 h) (HSFNT)
 450 Vac - D (1.000 h) (HSFQV)

RATED FREQUENCY:

50 – 60 Hz

Model 1: Typ: MK/MKA

Capacity uF	Dimensions ØxL (mm) without stud
1	25 x 60
1,5	25 x 60
2	25 x 60
2,5	30 x 60
3	25 x 60
4	30 x 60
5	30 x 60
6	30 x 60
7	30 x 60
8	30 x 70
10	35 x 70
12	35 x 70
14	35 x 70
16	40 x 70
18	40 x 95
20	40 x 70
25	40 x 95
30	40 x 95
35	45 x 95
40	45 x 95
45	50 x 95
50	50 x 95
60	50 x 120
70	50 x 120
80	50 x 120
90	60 x 120
100	55 x 120

Model 2: Typ: MKM

Capacity uF	Dimensions ØxL (mm) without stud
20	45 x 80
30	45 x 103
40	50 x 103
50	50 x 130
60	55 x 130

For further models please contact us directly



Delivery time: From stock