

Motor - Start - Capacitor

The motor starting capacitors are electrolytic capacitors with high capacitance value (in uF), able to provide a high starting torque to the motor. They are disconnected in the end of the starting process in order to avoid overload to the motor winding.

RATED VOLTAGE:	EL 250V – 250Vac EL 320V – 320Vac
RATED FREQUENCY:	50-60Hz
CASE:	plane base self-extinguishing (V2) plastic case
REFERENCE STANDARD:	EN60252 - VDE 560 / 8
WORKING TEMPERATURE:	-25 to +75 °C
EXECUTIONS:	double tag 6,3mm x 0,8mm, protective cap with cable output hole, fixing bracket and bipolar cable length 250mm

Capacity uF	Dimensions DxL (mm)	Operating Class
50 / 63 EL 320	47 x 95	1,7 %
63 / 80 EL 320	47 x 95	1,7 %
80 / 100 EL 320	47 x 95	1,7 %
100 / 125 EL 320	47 x 95	1,7 %
125 / 160 EL 320	47 x 95	1,7 %
160 / 200 EL 320	47 x 95	1,7 %
200 / 250 EL 320	47 x 95	1,7 %
250 / 315 EL 320	47 x 95	1,7 %
315 / 400 EL 250	47 x 95	1,7 %

Delivery time: From stock. For further models please contact us directly.

